

Product specification sheet on energy consumption

Passo XS style RLU

The following product data are compliant with the requirements of EU regulation no. 1185/2015 for the execution of directive 2009/125/EC and no. 1186/2015 and as amendment of directive 2010/30/EC.

| Technical data | lcon | Unit | Passo XS style RLU | | |
|---|-----------------|--|--------------------|--|--|
| Energy efficiency class | | | Α | | |
| Energieeffizienzindex | EEI | | 106.0 | | |
| Nominal output | P_{nom} | kW | 5.9 | | |
| Direct output | | kW | 5.9 | | |
| Indirect output | | kW | 0.0 | | |
| Thermal efficiency at nominal output | $\eta_{th,nom}$ | % | 80.0 | | |
| Use of auxiliary current at nominal output | el_{max} | kW | 0.0 | | |
| Use of auxiliary current at minimum output | el_{min} | kW | 0.0 | | |
| Use of auxiliary current in stand-by mode | el_{SB} | kW | 0.0 | | |
| Art der Wärmeleistung/Raumtemperaturkontrolle | Uncontro | Uncontrolled room temperature / single-level | | | |
| Preferred combustible | Moisture | Moisture content of split logs ≤ 25% | | | |
| Seasonal space heating energy efficiency (preferred fuel) | η_S | % | 70.0 | | |



Product specification sheet on energy consumption

Passo XS style mit S-Thermatik

The following product data are compliant with the requirements of EU regulation no. 1185/2015 for the execution of directive 2009/125/EC and no. 1186/2015 and as amendment of directive 2010/30/EC.

| Technical data | Icon | Unit | Passo XS style mit S- Thermatik |
|---|--|------|------------------------------------|
| Energy efficiency class | | | A+ |
| Energieeffizienzindex | EEI | | 107.0 |
| Nominal output | P_{nom} | kW | 5.9 |
| Direct output | | kW | 5.9 |
| Indirect output | | kW | 0.0 |
| Thermal efficiency at nominal output | $\eta_{th,nom}$ | % | 81.1 |
| Use of auxiliary current at nominal output | el_{max} | kW | 0.004 |
| Use of auxiliary current at minimum output | el_{min} | kW | 0.004 |
| Use of auxiliary current in stand-by mode | el_{SB} | kW | 0.003 |
| Art der Wärmeleistung/Raumtemperaturkontrolle | Uncontrolled room temperature / single-level | | |
| Preferred combustible | Moisture content of split logs ≤ 25% | | |
| Seasonal space heating energy efficiency (preferred fuel) | η_S | % | 70.8 |



Product specification sheet on energy consumption

Passo XS style

The following product data are compliant with the requirements of EU regulation no. 1185/2015 for the execution of directive 2009/125/EC and no. 1186/2015 and as amendment of directive 2010/30/EC.

| Technical data | Icon | Unit | Passo XS style | | |
|---|-----------------|--|----------------|--|--|
| Energy efficiency class | | | Α | | |
| Energieeffizienzindex | EEI | | 106.0 | | |
| Nominal output | P_{nom} | kW | 5.9 | | |
| Direct output | | kW | 5.9 | | |
| Indirect output | | kW | 0.0 | | |
| Thermal efficiency at nominal output | $\eta_{th,nom}$ | % | 80.0 | | |
| Use of auxiliary current at nominal output | el_{max} | kW | 0.0 | | |
| Use of auxiliary current at minimum output | el_{min} | kW | 0.0 | | |
| Use of auxiliary current in stand-by mode | el_{SB} | kW | 0.0 | | |
| Art der Wärmeleistung/Raumtemperaturkontrolle | Uncontro | Uncontrolled room temperature / single-level | | | |
| Preferred combustible | Moisture | Moisture content of split logs ≤ 25% | | | |
| Seasonal space heating energy efficiency (preferred fuel) | η_S | % | 70.0 | | |