



# Product specification sheet on energy consumption

## Senso L fashion

The following product data are compliant with the requirements of EU regulation no. 1185/2015 for the execution of directive 2009/125/EC and no. 1186/2015 and as amendment of directive 2010/30/EC.

| Technical data  | Icon   | Unit | Senso L fashion |
|---|--|------|-----------------|
| Energy efficiency class                                   |  |      | <b>A</b>        |
| Energieeffizienzindex                                     | EEI  |      | <b>106.0</b>    |
| Nominal output  | $P_{nom}$  | kW   | <b>7.0</b>      |
| Direct output   |  | kW   | <b>7.0</b>      |
| Indirect output   |  | kW   | <b>0.0</b>      |
| Thermal efficiency at nominal output                      | $\eta_{th,nom}$  | %    | <b>80.0</b>     |
| Use of auxiliary current at nominal output                | $el_{max}$   | kW   | <b>0.0</b>      |
| Use of auxiliary current at minimum output                | $el_{min}$   | kW   | <b>0.0</b>      |
| Use of auxiliary current in stand-by mode                 | $el_{SB}$  | kW   | <b>0.0</b>      |
| Art der Wärmeleistung/Raumtemperaturkontrolle             | <b>Uncontrolled room temperature / single-level</b>          |      |                 |
| Preferred combustible                                     | <b>Moisture content of split logs <math>\leq 25\%</math></b> |      |                 |
| Seasonal space heating energy efficiency (preferred fuel) | $\eta_S$   | %    | <b>70.0</b>     |



# Product specification sheet on energy consumption

## Senso L fashion 6,0 kW T 2.0

The following product data are compliant with the requirements of EU regulation no. 1185/2015 for the execution of directive 2009/125/EC and no. 1186/2015 and as amendment of directive 2010/30/EC.

| Technical data  | Icon   | Unit | Senso L fashion 6,0 kW T 2.0 |
|---|--|------|------------------------------|
| Energy efficiency class                                   |  |      | <b>A</b>                     |
| Energieeffizienzindex                                     | EEI  |      | <b>106.0</b>                 |
| Nominal output  | $P_{nom}$  | kW   | <b>6.0</b>                   |
| Direct output   |  | kW   | <b>6.0</b>                   |
| Indirect output   |  | kW   | <b>0.0</b>                   |
| Thermal efficiency at nominal output                      | $\eta_{th,nom}$  | %    | <b>80.0</b>                  |
| Use of auxiliary current at nominal output                | $el_{max}$   | kW   | <b>0.004</b>                 |
| Use of auxiliary current at minimum output                | $el_{min}$   | kW   | <b>0.004</b>                 |
| Use of auxiliary current in stand-by mode                 | $el_{SB}$  | kW   | <b>0.003</b>                 |
| Art der Wärmeleistung/Raumtemperaturkontrolle             | <b>Uncontrolled room temperature / single-level</b>          |      |                              |
| Preferred combustible                                     | <b>Moisture content of split logs <math>\leq 25\%</math></b> |      |                              |
| Seasonal space heating energy efficiency (preferred fuel) | $\eta_S$   | %    | <b>69.7</b>                  |



# Product specification sheet on energy consumption

## Senso L fashion 5,9 kW 2.0

The following product data are compliant with the requirements of EU regulation no. 1185/2015 for the execution of directive 2009/125/EC and no. 1186/2015 and as amendment of directive 2010/30/EC.

| Technical data  | Icon   | Unit | Senso L fashion 5,9 kW 2.0 |
|---|--|------|----------------------------|
| Energy efficiency class                                   |  |      | A                          |
| Energieeffizienzindex                                     | EEI  |      | 106.0                      |
| Nominal output  | $P_{nom}$                                    | kW   | 5.9                        |
| Direct output   |  | kW   | 5.9                        |
| Indirect output   |  | kW   | 0.0                        |
| Thermal efficiency at nominal output                      | $\eta_{th,nom}$                              | %    | 80.0                       |
| Use of auxiliary current at nominal output                | $el_{max}$                                   | kW   | 0.0                        |
| Use of auxiliary current at minimum output                | $el_{min}$                                   | kW   | 0.0                        |
| Use of auxiliary current in stand-by mode                 | $el_{SB}$                                    | kW   | 0.0                        |
| Art der Wärmeleistung/Raumtemperaturkontrolle             | Uncontrolled room temperature / single-level |      |                            |
| Preferred combustible                                     | Moisture content of split logs $\leq 25\%$   |      |                            |
| Seasonal space heating energy efficiency (preferred fuel) | $\eta_S$                                     | %    | 70.0                       |